

December 2, 2020

Klüber Lubrication NA LP • 9010 CR 2120, Tyler, Texas 75707, Phone +1 903.534.8021 • sales@klsummit.com

Product Data Sheet

NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

SYNTHETIC HYDRAULIC OIL

HySyn® FG Series

Summit HySyn® FG Series zinc-free ashless hydraulic oils are formulated specially for hydraulic systems operating in the food service, beverage, and packaging industry. These fully synthetic lubricants are NSF H1 Registered. HySyn® FG Series lubricants are Kosher approved and Halal certified. Summit is an ISO 21469 certified facility.

HySyn® FG lubricants are fortified with oxidation and corrosion inhibitors, as well as anti-wear additives to enhance the superior qualities offered by the synthetic hydrocarbon base stock. They are extended life lubricants and have the same excellent software compatibility as the Summit HySyn® Series hydraulic oils.

Physical Properties

PRODUCTS	FG-15	FG-22	FG-32	FG-46	FG-68	FG-100
ISO Grade	15	22	32	46	68	100
Viscosity						
@ 40°C, cSt	15.0	21.7	30.7	46.8	68.4	99.3
@ 100°C, cSt	3.58	4.56	5.80	7.79	10.4	13.9
@ 100°F, SUS	82	113	157	238	350	510
@ 210°F, SUS	38.3	41.6	45.7	52.3	61.5	74.9
Viscosity Index	122	127	134	135	139	141
Specific Gravity	0.816	0.821	0.830	0.834	0.838	0.841
Flash Point, °F	385	450	460	490	505	515
(°C)	(196)	(232)	(238)	(254)	(263)	(268)
Fire Point, °F	440	495	525	565	565	585
(°C)	(227)	(257)	(274)	(296)	(296)	(307)
Pour Point, °F	-103	-94	-81	-71	-65	-60
(°C)	(-75)	(-70)	(-63)	(-57)	(-54)	(-51)
Emulsion	40/40/0	40/40/0	40/40/0	40/40/0	40/40/0	40/40/0
Tendency	10 Mins	10 Mins	10 Mins	10 Mins	10 Mins	10 Mins
NSF Registered	H1	H1	H1	H1	H1	H1
ISO 21469	Yes	-	Yes	Yes	Yes	Yes
Kosher Approved	Yes	Yes	Yes	Yes	Yes	Yes
Halal Certified	Yes	Yes	Yes	Yes	Yes	Yes

Percent By Weight Phosphorous 0.0695 Sulfur 0.047

HySyn FG-46 does not produce an iridescent appearance (sheen) on the surface of the water when tested in accordance with the U.S. Coast Guard Static Sheen Test.

Shelf Life: Product shelf life is 5 years from the date of manufacture, after which the product should be recertified prior to use.

