

April 2, 2013

Klüber Lubrication NA LP • P.O. Box 131359 • Tyler, TX 75713, Phone 903.534.8021 • Fax 903.581.4376

# Product Data Sheet



NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

## FOOD GRADE AIR TOOLS

### LUBEAIR FG-22

*Lubeair FG-22 air line lubricant is formulated specifically for pneumatic tools used in the food service, beverage, and packaging industries. This lubricant is NSF Registered and meets U.S.D.A. 1998 (H1) guidelines (lubricants with possible incidental food contact). Summit is an ISO 21469 Certified facility.*

*Summit Lubeair FG-22 is fortified with a special additive package which gives it excellent oxidation stability and low temperature fluidity. It also contains an emulsifier for superior performance in high moisture environments*

### Physical Properties

PRODUCTS	LUBEAIR FG-22
ISO Grade	22
Viscosity	
@ 40°C, cSt	22.30
@ 100°C, cSt	4.30
Specific Gravity	0.860
Viscosity Index	96
Pour Point, °F (°C)	5 (-15)
Flash Point, °F (°C)	405 (207)
Fire Point, °F (°C)	440 (227)
Four Ball Wear Test, mm	0.54
Foaming:Seq. I, II, III	0/0
Copper Strip Corrosion	1A
Rust	Pass
NSF Registered	H1

**Shelf Life:** Product shelf life is 3 years from the date of manufacture, after which the product should be recertified prior to use.