

June 21, 2007

Klüber Lubrication NA LP • P.O. Box 131359 • Tyler, TX 75713, Phone 903.534.8021 • Fax 903.581.4376

# Product Data Sheet



NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

## PREMIUM SYNTHETIC BLEND

### PSV-22 VACUUM PUMP OIL

*Summit PSV-22 is formulated from a vacuum distilled ultra-pure paraffinic hydrocarbon base stock to provide an extremely low vapor pressure vacuum pump lubricant. This non-foaming fluid has excellent water separation and provides protection against wear, rust and corrosion. PSV-22 is an extended life lubricant designed to function in recirculating systems such as liquid ring vacuum pumps which are subject to severe temperature and environmental conditions.*

*Summit PSV-22 is compatible with commonly used seal and gasket materials.*

### Physical Properties

PRODUCT	PSV-22
ISO Grade	22
Viscosity	
@ 40°C, cSt	20.9
@ 100°C, cSt	4.19
@ 100°F, SUS	109.6
@ 210°F, SUS	40.4
Viscosity Index	103
Pour Point, °F (°C)	-27 (-33)
Flash Point, °F (°C)	380 (193)
Emulsion Tendency	40/38/2 (10 mins)
Copper Corrosion	1A

**Shelf Life:** Product shelf life is 3 years from the date of manufacture, after which the product should be recertified prior to use.